Recast

Recast Management Server Settings

Last Modified on 2026-08-05

On the **Settings** page you can select options for many plugins and for global settings that don't belong to a specific plugin.

To edit a setting, click the Edit icon to the right of the setting.

Active Directory

- **BitLockerSearchAd**: Default setting: True.
- **LapsSearchAd**: When enabled, the Retrieve All LAPS Passwords tool will retrieve LAPS passwords from Active Directory. Default value: True.
- **MaximumLapsExpirationTime**: The maximum time out that you can set the LAPS password expiration. This eliminates the possibility of a user accidentally setting a LAPS password to expire too far into the future. Default expiration time: 30 days.

Application Manager (now RCT Patching)

- **ApplicationCatalogUrl**: To access the RCT Patching application catalog. Set to https://amprod02.recastsoftware.com for Patching Enterprise, https://amprod01.recastsoftware.com for Patching Standard
- **CleanupApplicationsInterval**: Default value: Cleanup occurs every 10 minutes
- **ImportNewApplicationsInterval**: Default value: 30 minutes
- **SendEmailsInterval**: Default value: 10 minutes
- **UpdateCollectionInformationInterval**: Default value: 1 hour

ConfigMgr Server

- **BitLockerSearchConfigMgr**: When enabled, searches ConfigMgr for BitLocker recovery keys. Default value: True
- **NumberOfPackets**: Sets the number of WoL packets to send when trying to wake up devices. Default number of packets: 1
- **Unicast**: Determines if WoL packets are sent with unicast or subnet directed broadcasts. Default setting: false
- **WakeOnLanPort**: Sets the UDP port from which WoL packets will be sent. Default UDP port: 9

Global Settings

Includes settings that don't belong to a specific plugin.

- **DisplayLicensePromptsToUsers**: When enabled, end users see a license expiry warning in the Configuration Manager console if the Recast license is set to expire within 30 days. Default setting: false.
- **DisplayUpdatePromptsToUsers**: When enabled, end users see an update notification in the Configuration Manager console if Recast Software has released a newer software version. Default value: true. Switch this setting to 'false' if you update Right Click Tools using RCT Patching.
- **DisplayBugfixUpdatePromptsToUsers**: When enabled, end users see an update notification in the Configuration Manager console if Recast Software has released a newer minor software version that includes only bug fixes. Default value: false.
- **DNSReverseLookup**: Uses a DNS reverse lookup on the IP address that was returned by the ICMP echo request to make sure the device you're hitting is correct. This setting is disabled by default as reverse lookups aren't configured in default DNS installations. Default value: false.
- **MaxAuditLogAge**: Sets the amount of time to save audit log entries.
- **MaxInactiveAgentAge**: When the number of days of inactivity (defined as the number of days since the agent last connected to an agent gateway) exceeds the MaxInactiveAgentAge, the agent is automatically deleted. Default value: 90 days. Agent cleanup can be disabled by setting this option to 0 (zero).
  For all currently enrolled agents in the RMS database, upgrading to
- v5.9.2505.2003
  resets the Last Connected date to the current date, meaning that the count up to the defined MaxInactiveAgentAge restarts.

- **MaxSnapshotAge**: Sets the amount of time to save snapshot entries. Default value: 90 days.
- **PingComputerBeforeRunningTools**: Sends an ICMP Echo request to devices to check if the machine is on before running an action. This is a performance enhancement so Right Click Tools doesn't need to wait for WMI timeouts when devices are turned off. This setting should be disabled if ICMP echo is not allowed in your environment. Default setting: true.
- **ProvideAnalyticsDataToRecast**: Allows Right Click Tools to send crash reports and tool usage data to Recast Software. No identifiable information is sent to Recast Software. Default setting: true. Enterprise software customers can opt out of sharing analytics information with Recast. Community users do not have the option to disable the collection of usage data. For details about the data collected by Recast and its uses, see our privacy policy.
- **UseFQDN**: Determines if Right Click Tools uses the FQDN when attempting to run actions on computers. Default setting: true.
- **UseIPInsteadOfComputerName**: Determines if Right Click Tools uses the IP to attempt to run an action rather than the computer name. Default setting: false.
- **VerifyComputerNameViaWMI**: Queries WMI to determine if the computer name matches prior to running an action. Default setting: false.

MBAM

- **BitLockerSearchMBAM**: When enabled, searches MBAM for BitLocker recovery keys. Default value: True

Microsoft Graph

- **BitLockerSearchEntraID**: When enabled, searches Entra ID for BitLocker recovery keys. Default value: True
- **LapsSearchEntraId**: When enabled, the Retrieve All LAPS Passwords tool will retrieve LAPS passwords from Entra ID. Default value: True

PowerShell

- **EnablePSRemoting**: When a Run Script action is run in Recast Builder, this setting determines if that action tries to enable PS Remoting on the remote device, if required. Default setting: false.

Privilege Manager (now Privileged Access)

- **ForceHybridDevicestoOnPremAD**: When enabled, Privileged Access identifies settings for hybrid joined devices using existing Recast Management Server data rather than live directory queries that require Entra ID Proxy calls. Default setting: false.

Recast Management Server

- **Recast Agent Approval**: Sets the approval behavior when a Recast Agent connects to the Recast Management Server. Default behavior is to approve for: TrustedDomain.
- **Recast Agent Gateway Approval**: Sets the approval behavior when a Recast Agent Gateway connects to the Recast Management Server. Default behavior is to approve for: TrustedDomain.
- **Recast Proxy Approval**: Sets the approval behavior when a Recast Proxy connects to the Recast Management Server. Default behavior is to approve for: TrustedDomain.

Registry

- **Enable Remote Registry**: Allows Right Click Tools to enable the remote registry service when the registry plugin tries to connect to the registry of a device via Recast Builder actions. Default setting: false.

ServiceNow

- **ServiceNowInstanceURL**: Adds a ServiceNow web address, allowing your Recast Management Server to connect.

Task Scheduler

- **TaskResultMaxAge**: Sets the length of time that task results are stored. Default maximum age (in days): 30.

Recast