

Authorize a Proxy

Last Modified on 04.14.25

By default, the Recast Management Server automatically authorizes any Recast Proxy installed in the same domain as the Recast Management Server. Proxies installed in other domains must be approved manually, unless you've edited the [default setting to approve all proxies automatically](#).

Approve or Un-approve a Proxy Manually

If a [proxy is installed separately](#) in another domain, you must approve it manually.

To approve a proxy manually:

1. On the **Recast Proxies** page in your Recast Management Server, find your newly installed proxy. It should be visible but not **Authorized**.
2. Click the **Edit** icon to the right of the proxy.
3. In the **Edit** window, enable or disable the **Authorized** checkbox and click **Update**.

Recast Proxies

Computer Name	Connected	Version	Authorized	Actions
DEV1-RMSPROX-01	✓	5.8.2501.1312	✓	 
DEV2-RMSPROX-01	✓	5.8.2501.1312	✓	 
DEV3-RMSPROX-01	✓	5.8.2501.1312	✓	 

Approve All Proxies Automatically

You can choose to have your Recast Management Server automatically authorize all proxies regardless of the domain where they're installed.

To approve all proxies automatically:

1. In your Recast Management Server, navigate to **Administration > Settings**.
2. Under **Recast Management Server**, click the **Edit** icon to the right of **Recast Proxy Approval**.
3. In the Change Setting window, choose **Automatically Approve All Agents** from the **Value** drop-down menu.