



Global Deployment Process Settings for Intune

Last Modified on 01.21.25

Application Information

Application information settings are located on the Application Manager **Settings > Environment Settings** page.

Basic Application Information Settings

Application Name Format: The default naming format will display Publisher, Application, and Version information in that order (For example, Microsoft Office 365 v1.022.192).

To change the application name format:

1. On the **Environment Settings** page, click the **Deployment Processes** and **Basic** tabs.
2. Under **Application Name Format**, remove any categories you don't want to display in the application name by clicking the X next to the category.
3. Add one or more categories to the application name by choosing them from the drop-down menu.
4. Drag-and-drop the categories into the desired order.

To return the application name format to its default settings, click the **Reset to Recast defaults** icon.

Advanced Application Information Settings

On the **Deployment Processes > Advanced** tab, you can set an application category and add a description. You can also choose to feature a chosen application.

To set advanced application information settings:

1. On the **Environment Settings** page, click the **Deployment Processes** and **Advanced** tabs.
2. Select an application category from the drop-down.
3. Add a description. Maximum of 500 characters.
4. To display the software as a featured application, enable **Display as featured app**.
5. Enter an **Information URL**, a **Privacy URL**, and an **Owner**.
6. Add **Administrator Notes**. Maximum of 500 characters.

To return the category name or description to their default settings, click the **Reset to Recast defaults** icon.

Program

To set program options:

1. Set any **Additional Installation Parameters** or **Additional Uninstallation Parameters**.

Any additional installation parameters are appended to the default install/uninstall commands used by Application Manager. Additional parameters cannot be used to override the default installation commands.

All applications deployed by a deployment process where additional parameters are applied must be able to use the commands specified using this setting. We recommend creating an individual deployment process for each application that requires additional parameters, and then adding those commands to each of the newly-created deployment processes, rather than applying a global setting.

2. Select the **Device restart behavior**:

- Determine behavior based on return codes (default)
- No specific action
- App install may force a device restart
- Intune will force a mandatory device restart

3. Click the Edit icon to choose any **Groups excluded from deployment**.

4. Choose whether to **Allow the Available Uninstall**. By default, this option is set to **Yes**.
-

Cleanup

You can enable cleanup features for old application versions and set whether previous versions are automatically removed when the deployment of a newer version begins. By default, all cleanup options are set to **Yes**.

To set deployment process cleanup options, enable or disable the function to **Clean up previous versions**.

You can additionally choose to **Remove previous versions**, which automatically removes old application versions from Intune and removes files from the content location.

To set the deployment process cleanup interval:

1. In your Recast Management Server, navigate to **Administration > Settings**.

2. Under the Application Manager Plugin, set the **Cleanup Applications Interval**. By default, cleanup is set to occur every 10 minutes.

Supersedence

Applications Manager offers a number of settings to configure the supersedence rules around application versions.

To set supersedence options:

1. Choose to **Enable supersedence**: Default is **Yes**.

You can additionally choose to **Uninstall superseded applications before installation**: Default is **No**. Application Manager can update previous application versions without the uninstall option. The automatic task sequence update feature will not work if this option is set to **Yes**.

2. Select a **supersedence method**:

- **All previous versions** (default): Supersedes all previous versions that aren't removed
- **Previous version**: Supersedes only the previous version

3. Choose a **Maximum Allowed Runtime**: Set Hours and/or Minutes (cannot exceed 12 hours)

Return to Deployment Process Defaults

Reset All Deployment Processes to Default Settings

After the default deployment process configuration is set up, you might choose to set different options for other deployment processes. It's possible to return all deployment processes to default settings but doing so means that any custom settings will be lost.

To re-apply default settings to all deployment processes:

1. On the Application Manager **Settings** page, open the **Deployment Processes** tab.
2. Click **Reset all to default** and confirm the reset.

Reset Individual Settings to Defaults

To return an individual setting to its default, click the **Reset to Recast defaults** icon next to the setting.