

Open URL

Last Modified on 04.16.26

The *Open URL* action allows you to open an URL (optionally in a specific browser).

General

Type *Open URL*

Name Actions are easier to comprehend and manage over time when they have a suitable name that accurately expresses what they do.

URL www.example.com

Advanced

Specify which browser should open the web page. The following options are available:

- *Default* – the URL will be opened by the browser configured as default on devices.
- *Internet Explorer*
- *Firefox*
- *Chrome*
- *Opera*
- *Microsoft Edge*
- *Safari*
- *Recast* – the URL will be opened using the Recast browser.

Browser

When you select a specific browser to open the URL with and that browser is not available on the device, the URL will be opened in the default browser.

If this option is selected, then a background web request is made and no browser will be opened. This option is available only for Recast browser.

Hidden

Close after (seconds)

Set the number of seconds after which the Recast browser automatically closes.

Trust all URL schemes

If this option is selected, all URL schemes are considered safe.

Additional trusted URL schemes

For example vmware-view. The URLs can be separated by comma.

Shared authentication session

The Liquit session can be injected if opening a URL with a browser that is not yet authenticated to the Application Workspace.

Opens the URL in the selected browser, in private mode. The following browsers are supported with private mode:

Force private mode

- Internet Explorer 11
- Firefox
- Chrome
- Opera
- Edge (Chromium)



The Agent is required to open an URL in a specified browser. If no agent is running the URL will be opened in a new tab of the default browser configured on the device.

Supported platforms

Platform Supported

Web Yes

Windows Yes

macOS Yes

Recast
