Recast

Open URL

Last Modified on 2026-09-24

The *Open URL* action allows you to open an URL (optionally in a specific browser).

General	
Type	*Open URL*
Name	Give actions descriptive names that accurately convey what they do.
URL	www.example.com

Advanced	
Browser	Specify which browser should open the web page. The following options are available: • *Default* – the URL will be opened by the browser configured as default on devices. • *Internet Explorer* • *Firefox* • *Chrome* • *Opera* • *Microsoft Edge* • *Safari* • *Recast* – the URL will be opened using the Recast browser. When you select a specific browser to open the URL with and that browser is not available on the device, the URL will be opened in the default browser.
Hidden	If this option is selected, then a background web request is made and no browser will be opened. This option is available only for Recast browser.
Close after (seconds)	Set the number of seconds after which the Recast browser automatically closes.
Trust all URL schemes	If this option is selected, all URL schemes are considered safe.
Additional trusted URL schemes	For example vmware-view. The URLs can be separated by comma.
Shared authentication session	The Liquit session can be injected if opening a URL with a browser that is not yet authenticated to the Application Workspace.
Force private mode	Opens the URL in the selected browser, in private mode. The following browsers are supported with private mode: • Internet Explorer 11 • Firefox • Chrome • Opera • Edge (Chromium)

The Agent is required to open an URL in a specified browser. If no agent is running the URL will be opened in a new tab of the default browser configured on the device.

Recast

Supported platforms

Platform	Supported
Web	Yes
Windows	Yes
macOS	Yes