

Start process

Last Modified on 04.16.26

The *Start process* action allows you to execute a file.

General

Type *Start process*

Name Actions are easier to comprehend and manage over time when they have a suitable name that accurately expresses what they do.

Process Select the file you want to execute.

Arguments Insert the arguments for the file.

Directory Select the working directory.

Advanced

Context The level at which the action is executed *User*, *Device* or *Elevated user*. For elevated user, the action will be executed under the current user, but it's granted temporary permission to modify the local system. The way the process should be started:

Display

- *Normal* – the default Microsoft Windows settings are used.
- *Hidden* – the application will be launched hidden.
- *Minimized* – the application will be minimized at launch.
- *Maximized* – the application will be maximized at launch.

Wait for completion Determines if Liquit Workspace will wait before this action is finished before executing the next action.

Success return codes The return code that represents a successful execution of the action.

Redirect standard output to variable The temporary variable to which the standard output of a command line program is stored. This option is available only if **Display** is set to *Hidden*.

Redirect error output to variable The temporary variable to which the standard error of a command line program is stored. This option is available only if **Display** is set to *Hidden*.

Place return code in variable The temporary variable to which the return code of a command line program is stored.

Filters

Here you can define conditions which determine if the action will be executed. For more information, see [Filters](#).

In the **Edit output variable** dialog box you open by clicking on the browse button **...** of the **Redirect standard output to variable**, **Redirect error output to variable**, **Place return code in variable** fields, you can create new variables or change existing ones and use them to store the standard output, error output or return code. Note that the resulted variables exist only temporarily until the action is executed; they are not saved anywhere and they are displayed only in the package you configured them. After the action is executed, the variables are discarded.

Edit output variable dialog box

Element

Description

Variable

New or existing variable in which you want to store information.

- *Not sensitive* – The variable is logged in the log file and it is visible on Application Workspace UI.
- *Sensitive* – The variable is not logged in the log file and it is hidden on Application Workspace UI.

Sensitivity

- *Current variable sensitivity* – In case of an already existing variable, it takes its already configured sensitivity.

Recast

Element	Description
Trim value	Removes all whitespace from the front, end or both.
Append to existing value (if it exists)	It appends the new variable at the end of the existing one.



Agent
It requires the Agent to be running.

Supported platforms

Platform Supported

Web No
Windows Yes
macOS Yes
