

Uninstall MSI

Last Modified on 04.16.26

The *Uninstall MSI* action allows you to uninstall an MSI from devices.

General

Type *Uninstall MSI*

Name Actions are easier to comprehend and manage over time when they have a suitable name that accurately expresses what they do.

Uninstall MSI via path Uninstall applications that were installed by an MSI file by pointing to the same exact MSI file.

Uninstall MSI via Product Code Uninstall an MSI file just by knowing the unique product code of the MSI, without uploading the file to the client computers.

File The MSI file has to be available on the client to start the uninstall action.

Product Code This product code can be filled in manually or extracted from an existing MSI file from your local device. Directly extracting the product code from an MSI is available only for Windows OS.

Arguments Insert the arguments for the msiexec.exe

Advanced

Context The level at which the action is executed *User, Device or Elevated user*. For elevated user, the action will be executed under the current user, but it's granted temporary permission to modify the local system.

Network Credentials The network credentials from the credential store, which will be used to access the specified file on a network location. The option is available only for Windows.

Place return code in variable The temporary variable to which the return code of a command line program is stored.

Success return codes An optional prefilled field that lets you configure successful status codes for the install. You can adjust the value.

Filters

Here you can define conditions which determine if the action will be executed. For more information, see [Filters](#).

In the **Edit output variable** dialog box you open by clicking on the browse button **...** of the **Place return code in variable** field, you can create new variables or change existing ones and use them to store the return code. Note that the resulted variables exist only temporarily until the action is executed; they are not saved anywhere and they are displayed only in the package you configured them. After the action is executed, the variables are discarded.

Edit output variable dialog box

Element	Description
Variable	New or existing variable in which you want to store information. <ul style="list-style-type: none">• <i>Not sensitive</i> – The variable is logged in the log file and it is visible on Application Workspace UI.• <i>Sensitive</i> – The variable is not logged in the log file and it is hidden on Application Workspace UI.
Sensitivity	<ul style="list-style-type: none">• <i>Current variable sensitivity</i> – In case of an already existing variable, it takes its already configured sensitivity.
Trim value	Removes all whitespace from the front, end or both.
Append to existing value (if it exists)	It appends the new variable at the end of the existing one.



Agent

It requires the Agent to be running.

Recast

Supported platforms

Platform Supported

Web No

Windows Yes

macOS No
