Recast

Portal Settings

Last Modified on 2026-09-28

The portal screen allows you to configure global Application Workspace related settings.

Name: Title shown on the browser tab. By default, Application Workspace.

Logo

Logo Options:

- **Image** – Allows you to upload a custom logo.
- **Color** – The background color of the logo
  By default, the Application Workspace logo and color are displayed.

Portal

Portal Options:

- **Refresh interval** – This value represents the time interval between portal refreshes. By default, it is set to 1800.
- **Download Agent for Windows** – Make the **Download Agent** option available in the User Menu (for users) and the User Portal (for users and admins), on Windows devices.
  - **Disabled** – The **Download Agent** button is hidden.
  - **Universal Agent for Windows** – Universal Agent is distributed as a signed executable installer that supports both x86 and x64 architectures.
- **Download Agent for macOS** – Make the **Download Agent** option available in the User Menu (for users) and the User Portal (for users and admins), on macOS devices.
  - **Disabled** – The **Download Agent** button is hidden.
  - **Universal Agent for macOS** – Universal Agent is distributed as a signed .dmg installer that supports both x64 and ARM64 architectures.

Sessions

Session Option:

- **Session is eligible for clean up after being inactive for (seconds)** – Users are logged off of their session after the specified time of inactivity. The Clean Sessions scheduled task then deletes the session.

Packages

Package Options:

- **Default entitlement publish** – The default value of the **Publish** field, when adding a package entitlement.
- **Platforms** – Select the platforms to which you want to deploy packages.
- **Stages** – Enable/disable the Test and/or Acceptance stages within the package release management. Note that the Test and Acceptance stages are available only with a Release & Patch Management license.
- **Use trigger for user auto launch enabled apps** – Configure the trigger to use for starting packages that have been marked for auto launch by the user:
  - **Liquit logon** – Triggers when a user logs into the Application Workspace.
  - **User login** – Triggers when a user logs into the device.
- **Allow the Application Workspace Server to fetch the title and icon for a new web package** – Enables the Application Workspace Server to get the title and image of the website in the following two situations:
  - when an end user adds a link to a website directly in their **Workspace** tab. Via the **Add link** window.
  - when you create a **Web application** package.

Connectors

Recast

Connector Option:

- **Application Workspace connector identity scope** – Controls what packages are retrieved from a source zone configured for the Workspace connector.
  - **User** – Retrieves packages directly entitled to the connector–assigned user.
  - **User and everyone** (default) – Retrieves packages directly entitled to the connector–assigned user and to the built–in 'Everyone' group.
  - **All** – Retrieves packages directly entitled the connector–assigned user, the built–in 'Everyone' group, and to all identities which the connector–assigned user is member of (groups, contexts, collections etc.).

Notifications

Notification Options:

- **Send mail notifications as logged on user** – If enabled, the system will use the users' configured email addresses to send notifications for the report problem and app request – approval workflows. The configured mail server within Application Workspace must allow relaying or 'Send As' permissions for all users.
- **Report problem** – This option becomes available in the packages context menu only after this email address is filled in, allowing users to report issues to their system administrator. The configured mail server within Application Workspace requires 'Send As' permissions to send emails on behalf of the user.