

Server Settings

Last Modified on 04.16.26

Configure a proxy server that routes HTTP requests to the Application Workspace Server. All Application Workspace components within Application Workspace Server can use it, including identity sources and connectors.



Option availability

This option is visible for administrators with system-level permissions. They can manage the proxy server of the zone to which they are connected. To manage the proxy server of another zone, administrators must first connect to that zone.

Use proxy – Enable or disable the proxy server.

Proxy address – Insert the endpoint for accessing your proxy at a specific port.

Proxy credentials – Select an existing credential from your Credential Store.

Bypass proxy for local resources – If enabled, the local server instead of the proxy is used for the local resources.

Bypass proxy for the defined patterns – To bypass more complex addresses, you can set up exceptions for specific addresses in this table, or wildcards by listing them in full or a part of them using wildcards.

Add bypass proxy pattern



The following syntax can be used:

- workspace.recastsoftware.com - any schema, any port.
- https://workspace.recastsoftware.com - https schema, port 443
- workspace.recastsoftware.com:443 - any schema, port 443.
- https://*.recastsoftware.com:* - https schema, any port and any sub domain of recastsoftware.com (not including recastsoftware.com it self).
- *.* - any hostname, any port.

Bypass proxy pattern *

Confirm

Cancel