Recast

Configure Single Sign-On for Microsoft RDS

Last Modified on 2026-11-12

In order to set up Single Sign-On for Microsoft RDS, you'll need to create a credential template and then assign the credential at the connector level or the package level.

Prerequisites

- Application Workspace Agent
- Remote Desktop Protocol (RDP) files that are used for Single Sign-On must be signed
- For Application Workspace Agent to successfully initiate RemoteApp or desktop sessions via Microsoft RDS without relying on RDWeb, the target RDS host must be accessible over the public internet.
- When considering the location of apps within the target RDS host, note that the target RDS host has a one-level folder hierarchy.

To facilitate SSO authentication for a new package imported from the RDS connector we need to create a "Credential" entity in the Application Workspace.

Create a credential template in Application Workspace

1. Navigate to **Manage** > **Authentication** > **Credential Store** and click **Create**.
2. In the **Create credential** window that opens:
    - For the **Type**, select 'Template' and click **Next**
    - In **Overview**, insert a name and description for your template
    - For **Credentials**, specify a variable username and a variable password for the SSO authentication. Choose whether you want to verify the provided password. Password will be verified when the user enters their credentials.
3. Navigate to the package imported from the RDS connector and open it.
4. Navigate to **Releases** > **Actions**.

Assign the credential

The credential template can be assigned in two ways. At the connector level and all packages that are imported will inherit the credential. Or you can overwrite the connector credential and assign it directly to a package.

At the RDS connector level
In the RDS connector > **Settings** screen > the **Network Credentials** field.

At package level
It can be assigned only to actions that support a device context.

1. Create a package from the Application Workspace Setup Store manually or import apps through the synchronization method.
2. Navigate to **Releases** > **Actions**.
3. Edit or create a new action that supports a device context.

Recast

4. In the **Advance** tab of the action:
    - In **Context**, select *Device*.
    - In **Network Credentials**, select the credential template you previously created.

> Managed packages
> Note that in the case of managed packages, existing actions cannot be edited nor deleted. To do so, you must convert the package to unmanaged by clicking on **Modify package** at the top of the **Overview** screen.
>
> 
>

Further reading

Set up the Remote Desktop web client for your users (Microsoft documentation)