

Liquit.Catalog.Get

Last Modified on 04.16.26

The *Liquit.Catalog.Get* function returns all information on an application in the user catalog. Whenever an application has been made available in the **Catalog** it will be available in the response of this function.

Request parameters

The following parameters are available for the API:

Name	Description	Value
id	The GUID needed to request the application	<GUID>
reviews	If true, reviews will be included in the response (available for Application Workspace 3.6 and later)	<boolean>
media	If true, media will be included in the response (available for Application Workspace 3.6 and later)	<boolean>
faq	If true, the frequently asked questions will be included in the response (available for Application Workspace 3.6 and later)	<boolean>

Return parameters

The following properties are returned:

Name	Description	Value
active	Determines whether or not the application is active. If this is true, the application was already successfully requested.	<boolean>
categories	Returns an array containing all categories associated with the application.	<array[]>
icon	Returns the URL of the application icon.	<string>
id	The GUID of the application.	<guid>
name	The friendly name of the application.	<string>
rating	The global rating of the application.	<int>
status	The status of the application: <ul style="list-style-type: none"><i>active</i> – The application has been requested and approved<i>available</i> – The application can be requested and no approval workflow is configured, meaning it becomes available in the workspace immediately<i>pending</i> – The application has been requested, however, an approval is still needed	<string>

Example

```
var id = '00000000-0000-0000-0000-000000000000';
// Catalog get
Liquit.Catalog.Get({
  id:id,
  media: true,
  license: true,
  reviews: true,
  faq: true
}, function (fault, result) {
  console.log(result)
});
```