

Liquit.Settings.List

Last Modified on 04.16.26

The *Liquit.Settings.List* function returns all user and portal settings available. Some properties are read-only; for more details, see [the list with all properties](#).

Usage

Every setting has at least four different properties:

- *id* – The identifier of the setting (e.g. “portal.animations” identifies whether or not animations are enabled)
- *force* – Reflects whether or not an administrator has locked a user setting in Application Workspace >**Manage** > **User Settings**.
- *inherited* – This property reflects whether or not the value is inherited or if it is modified
- *value* – Returns the value of the setting.

Example

```
Liquit.Settings.List(function (fault, result) {

    // Check if the request failed.
    if (fault != null) {
        alert('Error ' + fault.code + ': ' + fault.message);
        return;
    }

    // The result object contains an array with all the settings.
    console.log(result)

    // Build a table with all the available settings and their values.
    var table = $('<table>')
    .append(
        $('<tr>').append(
            $('<td>')
            .text('Setting id'),
            $('<td>')
            .text('Value'),
            $('<td>')
            .text('Force'),
            $('<td>')
            .text('Inherited')
        )
    );

    // Loop through result.
    for (var i in result)
        table.append(
            $('<tr>').append(
                $('<td>').text(result[i].id),
                $('<td>').text(result[i].value),
                $('<td>').text(result[i].force),
                $('<td>').text(result[i].inherited)
            )
        )

    table.appendTo($('body'));

});
```

Recast
