

Devices

Last Modified on 04.16.26

Get-LiquitDevice

Synopsis

This command displays a list of all devices from the Application Workspace.

Syntax

```
Get-LiquitDevice  
[-LiquitContext <LiquitContext>]  
[<CommonParameters>]
```

```
Get-LiquitDevice  
[-ID] <guid[]>  
[-LiquitContext <LiquitContext>]  
[<CommonParameters>]
```

```
Get-LiquitDevice  
[-IdentityRef] <IdentityRef[]>  
[-LiquitContext <LiquitContext>]  
[<CommonParameters>]
```

```
Get-LiquitDevice  
[-Search] <string>  
[-LiquitContext <LiquitContext>]  
[<CommonParameters>]
```

```
Get-LiquitDevice  
[-Name] <string>  
[-LiquitContext <LiquitContext>]  
[<CommonParameters>]
```

Examples

This command lists all devices available within the Application Workspace:

```
Get-LiquitDevice
```

This command will select the device with the ID 00000000-0000-0000-0000-000000000000:

```
Get-LiquitDevice -id 00000000-0000-0000-0000-000000000000
```

Parameters

Name	Value	Description	Required	Default value
------	-------	-------------	----------	---------------

Recast

Name	Value	Description	Required	Default value
Search	<code><string></code>	This parameter serves a similar purpose to the search box found in the devices table from the Application Workspace UI. It enables users to search multiple columns within the table, such as Name and Agent type. When a search term is provided, the parameter filters records by matching values in these indexed columns. However, it's important to note that not all columns in the table are indexed, meaning that searches for values in these non-indexed columns will not return results. Non-indexed columns include for example the ID and columns containing checkboxes.		
Name	<code><string></code>	Searches on the device name itself.		
LiquitContext	<code><LiquitContext></code>	Determines the selected zone.	No	Default

Start-LiquitWakeDevice

Synopsis

This command wakes a device.

Syntax

```
Start-LiquitWakeDevice  
[-ID] <guid[]>  
[-LiquitContext <LiquitContext>]  
[<CommonParameters>]
```

```
Start-LiquitWakeDevice  
[-Device] <Device[]>  
[-LiquitContext <LiquitContext>]  
[<CommonParameters>]
```

Example

This command wakes the device with the ID 00000000-0000-0000-0000-000000000000:

```
Start-LiquitWakeDevice -id 00000000-0000-0000-0000-000000000000
```

Parameters

Name	Value	Description	Required	Default value
Device	<code><Device[]></code>	The device that should be woken.	Yes	
ID	<code><guid[]></code>	The id of the device that should be woken.	Yes	
LiquitContext	<code><LiquitContext></code>	Determines the selected zone.	No	Default

Remove-LiquitDevice

Synopsis

Removes a device from the Application Workspace.

Syntax

```
Remove-LiquitDevice  
[-Device] <Device[]>  
[-LiquitContext <LiquitContext>]  
[-WhatIf]  
[-Confirm]  
[<CommonParameters>]
```

Example

The following script removes the selected device from the Application Workspace:

```
$device = Get-LiquitDevice -id 00000000-0000-0000-0000-000000000000  
Remove-LiquitDevice -Device $device
```

Parameters

Name	Value	Description	Required	Default value
Device	<Device[]>	The device that should be removed.	Yes	
LiquitContext	<LiquitContext>	Determines the selected zone.	No	Default
