

User Collections

Last Modified on 04.16.26

Get-LiquitUserCollection

Synopsis

This command displays a list of all user collections from the Application Workspace, or you can select a specific user collection.

Syntax

```
Get-LiquitUserCollection  
[-LiquitContext <LiquitContext>]  
[<CommonParameters>]
```

```
Get-LiquitUserCollection  
[-ID] <guid[]>  
[-LiquitContext <LiquitContext>]  
[<CommonParameters>]
```

```
Get-LiquitUserCollection  
[-IdentityRef] <IdentityRef[]>  
[-LiquitContext <LiquitContext>]  
[<CommonParameters>]
```

```
Get-LiquitUserCollection  
[-Search] <string>  
[-LiquitContext <LiquitContext>]  
[<CommonParameters>]
```

```
Get-LiquitUserCollection  
[-Name] <string>  
[-LiquitContext <LiquitContext>]  
[<CommonParameters>]
```

Examples

The following command lists all available user collections within Application Workspace.

```
Get-LiquitUserCollection
```

The following command lists a specific user collection.

```
Get-LiquitUserCollection -id 00000000-0000-0000-0000-000000000000
```

New-LiquitUserCollection

Synopsis

This command creates a new user collection.

Syntax

```
New-LiquitUserCollection
  -Dynamic
  -Name <string>
  -Filters <ContextFilters>
  [-Description <string>]
  [-LiquitContext <LiquitContext>]
  [-WhatIf]
  [-Confirm]
  [<CommonParameters>]
```

```
New-LiquitUserCollection
  -Dynamic
  -Name <string>
  -Script <string>
  [-Description <string>]
  [-LiquitContext <LiquitContext>]
  [-WhatIf]
  [-Confirm]
  [<CommonParameters>]
```

```
New-LiquitUserCollection
  -Dynamic
  -Name <string>
  [-Description <string>]
  [-LiquitContext <LiquitContext>]
  [-WhatIf]
  [-Confirm]
  [<CommonParameters>]
```

```
New-LiquitUserCollection
  -Name <string>
  [-Description <string>]
  [-LiquitContext <LiquitContext>]
  [-WhatIf]
  [-Confirm]
  [<CommonParameters>]
```

Example

The following command creates a new user collection, named " UserCollection".

```
New-LiquitUserCollection - Name " UserCollection"
```

Parameters

| Name | Value | Description | Required | Default value |
|---------------|------------------|--|----------|---------------|
| Dynamic | | Create a dynamic user collection. | Yes | |
| Name | <string> | Provide a name for the user collection. | Yes | |
| Script | <string> | The script to use for the user collection. | Yes | |
| Filters | <ContextFilters> | Filters to use for the user collection. | Yes | |
| Description | <string> | Provide a description for the user collection. | No | |
| LiquitContext | <LiquitContext> | Determines the selected zone. | No | Default |

Recast

Set-LiquitUserCollection

Synopsis

This command updates a user collection.

Syntax

```
Set-LiquitUserCollection
  [-UserCollection] <UserCollection[]>
  [-Name <string>]
  [-Description <string>]
  [-Filters <ContextFilters>]
  [-LiquitContext <LiquitContext>]
  [-WhatIf]
  [-Confirm]
  [<CommonParameters>]
```

```
Set-LiquitUserCollection
  [-UserCollection] <UserCollection[]>
  [-Name <string>]
  [-Description <string>]
  [-Script <string>]
  [-LiquitContext <LiquitContext>]
  [-WhatIf]
  [-Confirm]
  [<CommonParameters>]
```

Example

The following command updates the name of the user collection to "Updated UserCollection".

```
$UserCollection = Get-LiquitUserCollection -id 00000000-0000-0000-0000-000000000000
Set-LiquitUserCollection -UserCollection $UserCollection -Name "Updated UserCollection"
```

Parameters

| Name | Value | Description | Required | Default value |
|----------------|--------------------|--|----------|---------------|
| UserCollection | <UserCollection[]> | The user collection that needs to be updated. | Yes | |
| Name | <string> | Provide a name for the user collection. | Yes | |
| Script | <string> | Script to use for the user collection. | No | |
| Filters | <ContextFilters> | Filters to use for user collection. | No | |
| Description | <string> | Provide a description for the user collection. | No | |
| LiquitContext | <LiquitContext> | Determines the selected zone. | No | Default |

Remove-LiquitUserCollection

Synopsis

Removes a user collection from the Application Workspace.

Syntax

```
Remove-LiquitUserCollection  
[-UserCollection] <UserCollection[]>  
[-LiquitContext <LiquitContext>]  
[-WhatIf]  
[-Confirm]  
[<CommonParameters>]
```

Example

The following command removes the selected device collection from the Application Workspace.

```
$UserCollection = Get-LiquitUserCollection -id 00000000-0000-0000-0000-000000000000  
Remove-LiquitUserCollection -UserCollection $UserCollection
```

Parameters

| Name | Value | Description | Required | Default value |
|----------------|--------------------|---|----------|---------------|
| UserCollection | <UserCollection[]> | The user collection that should be removed. | Yes | |
| LiquitContext | <LiquitContext> | Determines the selected zone. | No | Default |
