Recast

Tags

Last Modified on 2026-11-02

Get-LiquitTag

This command displays a list of all the tags available within Application Workspace. Alternatively, you can select a specific tag.

Syntax

```
Get-LiquitTag
[-LiquitContext <LiquitContext>]
[<CommonParameters>]

Get-LiquitTag
[-ID] <guid[]>
[-LiquitContext <LiquitContext>]
[<CommonParameters>]

Get-LiquitTag
[-EntityRef] <EntityRef[]>
[-LiquitContext <LiquitContext>]
[<CommonParameters>]

Get-LiquitTag
[-Type] {Workspace | Management}
[-LiquitContext <LiquitContext>]
[<CommonParameters>]

Get-LiquitTag
  [-Search] <string>
  [-LiquitContext <LiquitContext>]
  [<CommonParameters>]

Get-LiquitTag
  [-Name] <string>
  [-LiquitContext <LiquitContext>]
  [<CommonParameters>]
```

Examples

This command displays all tags defined within Application Workspace:

```
Get-LiquitTag
```

This command displays the selected tag:

```
Get-LiquitSetting -id 00000000-0000-0000-0000-000000000000
```

Parameters

Name	Value	Description	Required	Default value

Name	Value	Description	Required	Default value
Type	`{Workspace | Management}`	The type of the tag • Workspace: This tag is visible within the users workspace. • Management: This tag is only visible within the management interface for administrators.		
Search	`<string>`	This parameter serves a similar purpose to the search box found in the tags table from the Application Workspace UI. It enables users to search multiple columns within the table, such as Name and Type. When a search term is provided, the parameter filters records by matching values in these indexed columns. However, it's important to note that not all columns in the table are indexed, meaning that searches for values in these non-indexed columns will not return results. Non-indexed columns include for example the ID and columns containing checkboxes.		
Name	`<string>`	Searches on the tag name itself.		
LiquitContext	`<LiquitContext>`	Determines the selected zone.	No	Default

New-LiquitTag

This command creates a new tag.

Syntax

```
New-LiquitTag
[-Name] <string>
[-Type] {Workspace | Management}
[-Color <string>]
[-Description <string>]
[-Icon <Content>]
[-LiquitContext <LiquitContext>]
[-WhatIf]
[-Confirm]
[<CommonParameters>]
```

Example

This creates a new tag named “PowerShell Tag”, of the “Workspace” type:

```
New-LiquitTag -Name "PowerShell Tag"  -Type "Workspace"
```

Parameters

Name	Value	Description	Required	Default value

Recast

Name	Value	Description	Required	Default value
Name	`<string>`	The name of the tag to be created.	Yes	
Type	`{Workspace | Management}`	The type of the tag • Workspace: This tag is visible within the users workspace. • Management: This tag is only visible within the management interface for administrators.	Yes	
Color	`<string>`	The color used for the tag. The value should be a hex value (e.g. 15a4fa).	no	
Description	`<string>`	The description of the tag.	no	
Icon	`<Content>`	The icon of the tag.	no	
LiquitContext	`<LiquitContext>`	Determines the selected zone.	No	Default

Set-LiquitTag

This command lets you edit the properties of a tag.

Syntax

```
Set-LiquitTag
[-Tag] <Tag[]>
[-Name <string>]
[-Type {Workspace | Management}]
[-Color <string>]
[-Description <string>]
[-Icon <Content>]
[-LiquitContext <LiquitContext>]
[-WhatIf]
[-Confirm]
[<CommonParameters>]
```

Example

This command updates the tag:

```
$tag = Get-LiquitTag -id 00000000-0000-0000-0000-000000000000
Set-LiquitTag -Name "Updated PowerShell Tag" -Color "15a4fa" -Tag $tag
```

Parameters

Name	Value	Description	Required	Default value
Tag	`<Tag[]>`	The tag to be updated.	Yes	

Recast

Name	Value	Description	Required	Default value
Name	`<string>`	The name of the tag to be created.	No	
Type	`{Workspace | Management}`	The type of the tag • Workspace: This tag is visible within the users workspace. • Management: This tag is only visible within the management interface for administrators.	No	
Color	`<string>`	The color used for the tag. The value should be a hex value (e.g. 15a4fa).	no	
Description	`<string>`	The description of the tag.	no	
Icon	`<Content>`	The icon of the tag	no	
LiquitContext	`<LiquitContext>`	Determines the selected zone.	No	Default

Remove-LiquitTag

This command removes a tag.

Syntax

```
Remove-LiquitTag
[-Tag] <Tag[]>
[-LiquitContext <LiquitContext>]
[-WhatIf]
[-Confirm]
[<CommonParameters>]
```

Example

The following script removes the specified tag:

```
$tag  = Get-LiquitTag -ID 00000000-0000-0000-0000-000000000000
Remove-LiquitTag -Tag $tag
```

Parameters

Name	Value	Description	Required	Default value
Tag	`<Tag[]>`	The tag you want to remove.	Yes	
LiquitContext	`<LiquitContext>`	Determines the selected zone.	No	Default
