Recast

Package Shortcuts

Last Modified on 2026-11-02

Get-LiquitPackageShortcut

This command displays a list of all shortcuts associated with a package. Alternatively, you can use this command to select a specific shortcut.

Syntax

```
Get-LiquitPackageShortcut
   [-Snapshot] <PackageSnapshot>
   [-LiquitContext <LiquitContext>]
   [<CommonParameters>]

Get-LiquitPackageShortcut
   [-Snapshot] <PackageSnapshot>
   [-ID] <string[]>
   [-LiquitContext <LiquitContext>]
   [<CommonParameters>]

Get-LiquitPackageShortcut
   [-Snapshot] <PackageSnapshot>
   [-Search] <string>
   [-LiquitContext <LiquitContext>]
   [<CommonParameters>]

Get-LiquitPackageShortcut
   [-Snapshot] <PackageSnapshot>
   [-Name] <string>
   [-LiquitContext <LiquitContext>]
   [<CommonParameters>]
```

Parameters

Name	Value	Description	Required	Default value
Search	`<string>`	This parameter serves a similar purpose to the search box found in the shortcuts table within a package, from the Application Workspace UI. It enables users to search multiple columns within the table, such as Display name and Deschiption. When a search term is provided, the parameter filters records by matching values in these indexed columns. However, it's important to note that not all columns in the table are indexed, meaning that searches for values in these non-indexed columns will not return results. Non-indexed columns include for example columns containing checkboxes.	Yes	
Name	`<string>`	Searches on the package shortcut name itself.	No	
LiquitContext	`<LiquitContext>`	Determines the selected zone.	No	Default

Recast

New-LiquitPackageShortcut

This command associates a new shortcut with a package.

Syntax

```
New-LiquitPackageShortcut
   [-Snapshot] <PackageSnapshot>
   [-ID] <string>
   [-Name] <string>
   [-Description <string>]
   [-Enabled <bool>]
   [-Icon <Content>]
   [-LiquitContext <LiquitContext>]
   [-WhatIf]
   [-Confirm]
   [<CommonParameters>]
```

Parameters

Name	Value	Description	Required	Default value
Snapshot	`<string>`	The snapshot to which you want to add the shortcut.	Yes	
ID	`<string>`	The ID of the package shortcut.	Yes	
Name	`<string>`	Provide a name for the package shortcut.	Yes	
Description	`<string>`	Provide a description for the package shortcut.	No	
Enabled	`<bool>`	Determines whether or not the package shortcut is enabled.	No	False
Icon	`<Content>`	The icon of the team.	No	
LiquitContext	`<LiquitContext>`	Determines the selected zone.	No	Default

Set-LiquitPackageShortcut

This command lets you edit the properties of a shortcut for a package.

Syntax

```
Set-LiquitPackageShortcut
   [-Shortcut] <PackageShortcut[]>
   [-Name <string>]
   [-Description <string>]
   [-Enabled <bool>]
   [-Icon <Content>]
   [-LiquitContext <LiquitContext>]
   [-WhatIf]
   [-Confirm]
   [<CommonParameters>]
```

Parameters

Name	Value	Description	Required	Default value
Shortcut	`<string>`	The package shortcut to be updated.	Yes	
Name	`<string>`	Provide a name for the package shortcut.	No	
Description	`<string>`	Provide a description for the package shortcut.	No	
Enabled	`<bool>`	Determines whether or not the package shortcut is enabled.	No	False
Icon	`<Content>`	The icon of the team.	No	
LiquitContext	`<LiquitContext>`	Determines the selected zone.	No	Default

Remove-LiquitPackageShortcut

This command removes a shortcut from a package.

Syntax

```
Remove-LiquitPackageShortcut
   [-Shortcut] <PackageShortcut[]>
   [-LiquitContext <LiquitContext>]
   [-WhatIf]
   [-Confirm]
   [<CommonParameters>]
```

Parameters

Name	Value	Description	Required	Default value
Shortcut	`<string>`	The shortcut you wish to remove.	Yes	
LiquitContext	`<LiquitContext>`	Determines the selected zone.	No	Default
