Recast

Log

Last Modified on 2026-11-04

The Application Workspace Agent logs events it initiates.

```
{
   "log": {
      "level": "Debug",
      "agentPath": "Agent.log",
      "userHostPath":"UserHost.log",
      "rotateCount": 5,
      "rotateSize": 1048576
   }
}
```

Key	Description	Default
level	This element is used to define the level of logging. The following levels are available: • *None* – Nothing will be logged to the log file • *Critical* – Only critical errors will be logged to the log file. • *Error* – Only errors and critical errors will be logged to the log file. • *Warning* – Only warnings, errors and critical errors will be logged to the log file. • *Info* – Basic information, warnings, errors and critical errors will be logged to the log file. • *Debug* – Detailed information about all actions, including all web activity will be logged to the log file. You can use this information when troubleshooting.	Info
agentPath	You can define an alternate path of the Agent log files here. The default location is: • Windows: *%ProgramData%\Liquit\Agent\Logs\Agent.log* • macOS: */Library/Logs/com.liquit.Agent/Agent.log*	Agent.log
userHostPath	You can define an alternate path of the userhost log files here. The default location is: • Windows: *%LOCALAPPDATA%\Liquit\UserHost\Logs\UserHost.log* • macOS: */Users/xxx/Library/Logs/com.liquit.Agent/UserHost.log*	UserHost.log
rotateCount	The number of logfiles that will be archived.	5
rotateSize	The limit of logfile size in bytes. When this limit is reached, a new logfile will be created and the old file will be archived.	