Recast

Launcher

Last Modified on 2026-11-04

Options that control Application Workspace Launcher behaviour.

```
{
   "launcher": {
      "enabled": true,
      "state": "Default",
      "start": "Auto",
      "tiles": false,
      "minimal": false,
      "contextMenu": true,
      "sideMenu": "Tags",
      "close": true
      "startupDelayMilliseconds": 5000
      }
}
```

Keys	Description	Default
enabled	Enables the background service of the Application Workspace Launcher.	true
state	Defines how the Application Workspace Launcher will be shown upon startup: • Default – Default sized window • Minimized – Minimized window • Maximized – Maximized window	Default
start	Defines when the launcher is visible and accessible to the user: • Disabled – Application Workspace Launcher does not open during login. • Auto – Application Workspace Launcher opens when connected to the zone or offline mode is available. • Connected – Application Workspace Launcher opens when connected to the zone. • Always – Application Workspace Launcher always opens, even if connection to the zone fails or offline mode isn't available. For Windows OS, the configuration of this option overrides the Windows Startup configuration. This means that even if you disable the Application Workspace Launcher in the Windows Startup list, the launcher will still start automatically when you log in, as long as this setting has a value different than *Disabled*.	Auto
tiles	If set to *true*, Application Workspace will use the tile-themed skin.	false
minimal	If set to *true*, the Side Menu and tabs (**Workspace**, **Contacts**, **Catalog**, **Manage**) are hidden. Only the toolbar without the side menu toggler is displayed.	false
contextMenu	If set to *true*, the context menu is available across Application Workspace Launcher.	true
sideMenu	Choose which tab(s) should be opened by default in the Side Menu.: • filters • tags • teams • categories	

Recast

Keys	Description	Default
close	If set to *false*, the **X** close button of the Application Workspace Launcher window is disabled and the quit option from the icon's context menu in the system tray is hidden.	true
startupDelayMilliseconds	The startup delay is applied only when UserHost is launched at system startup; if the user closes the UI and starts it again manually, the UI opens immediately and the delay is not applied.	0